



Asset-Trade

Assessment & Sale of Used Assets

Ref. No.: 1416-04171752

Overview and Technical Data:

**Band new HERKULES WSE 180 x 1500 CNC
Roller grinder**

HERKULES

 **HERKULES**

Year of Build: Mar 1996



Description:

Band new HERKULES WSE 180 x 1500 CNC Roller grinder

Still in original wooden packaging

Zero Running hours

Technical Data :

- Power: 70 kW
- Workspace:
 - max. grinding diameter: 360 mm
 - min. grinding diameter: 0 mm
 - max. center distance: 1500 mm
 - max. roller weight in steady rests: 700 kg
- Headstock
 - Roller speeds, continuously adjustable: 16-160 rpm
 - Transistor-controlled three-phase servo motor max. torque: 27 Nm
- Tailstock
 - with hand-operated adjustment device: for longitudinal movement of the tailstock on the machine table
 - with mechanical, conical clamping elements: for clamping the tailstock in any position
- Grinding table
 - Travel speed, continuously adjustable: 50-3000 mm/min
 - frequency-controlled three-phase servo drive: 14 Nm
 - Guideway lubrication: combined hydrodynamic/forced lubrication to avoid the typical floating effects of hydrostatic lubrication

The following grinding wheel feed types are included:

- Motor-driven rapid feed (X-axis): 400 mm/min
- Motor-driven fine feed (X-axis) exact: 0.01mm
- Automatic feed in the reversing points (X-axis), preselectable: 0.01 -0.09 mm
- Automatic feed in the reversing points (F-axis), preselectable: 0.001 -0.01 mm
- Continuous feed to compensate for grinding wheel wear, for working with constant power (X-axis), preselectable 0.01 -0.2 mm/min



- Automatic feed limitation with automatic feed shutdown, digital, when preselected values ??are reached
- Automatic attachment of the wheel to the roller with X-axis feed,
- shutdown and automatic initiation of the Z-axis feed.
- Including:
 - Automatic safety retraction of the
 - disk at preselected ampere levels
 - Overload overspeed
 - Power failure
- Manual microfeed

Accuracy: 0.001 mm

- a) Hollow and bellows grinding option
- b) light
- particularly at the ends of the barrel to relieve pressure
- in the rolling mill: 1 mm on diameter
- Cone grinding
- 9. Reset device for automatically repositioning the grinding disc on the roller
- after a grinding process interruption
- (e.g. measuring) with a repositioning
- accuracy of: 0.001 mm



Technical Data:

Technical Data:

Control: CNC

Machine Hours: 0

Buyer Information:

Condition: Like New

Available: Immediately

Sold as:

Free Loaded on Truck (LOT)


VAT: 19 %

Buyers Premium: 18 %

Location: Germany



Images:





Asset-Trade

Assessment & Sale of Used Assets

QR Code for <https://www.asset-trade.de/en/print/pdf/node/7790?la>

Asset-Trade

**Assessment and Sale of Used Assets world
wide**

Am Sonnenhof 16

47800 Krefeld

Germany

Tel.: +49 2151 32500 33